

Monster Truck Loaders

Truck Loaders will attack debris with ease. These monstrous machines allow you to fit more into a truck or trailer and clear more properties between offloads for higher productivity and more profit.



INDUSTRY LEADING 15 TO 1 REDUCTION RATIO



FEATURES

- 14HP Subaru® EX40 engine
- 5/16" thick 16" diameter steel teathed impeller
- 2803 cfm
- Tool-free 360-degree discharge chute adjustment
- 8" x 10' Flexible urethane intake hose increases volume
- Polymer discharge chute (with liner) (7" x 30")

Mounting Options:

- Skid (standard)
- Optional: Hitch, Swing-Away or Tailgate



FEATURES

- 18HP Briggs & Stratton® Vanguard™ engine / electric start
- 3/8" thick 20" diameter steel teathed impeller
- 3510 cfm
- Stack gaskets seal in airflow and lock in debris moisture
- 10" x 10' Flexible urethane intake hose increases volume
- Metal discharge chute (7" x 30")

Mounting Options:

- Skid or Swing-Away Hitch



FEATURES

- 29HP Briggs & Stratton® Vanguard™ engine / electric start
- 3/8" thick 20" diameter steel teathed impeller
- 4710 cfm
- Stack gaskets seal in airflow and lock in debris moisture
- 12" x 10' Flexible urethane intake hose increases volume
- Flex-Tube discharge chute (8" x 5')

Mounting Options:

- Skid or Tow-behind



FEATURES

- 35HP Briggs & Stratton® Vanguard™ engine / electric start
- 1/2" thick 25" diameter steel teathed impeller
- 6950 cfm
- Stack gaskets seal in airflow and lock in debris moisture
- 16" x 10' Flexible urethane intake hose increases volume
- Metal discharge chute (12" x 6')

Mounting Options:

- Skid or Tow-Behind



FEATURES

- 36HP Yanmar® Diesel engine / electric start
- 1/2" thick 25" diameter steel teathed impeller
- 7450 cfm
- Stack gaskets seal in airflow and lock in debris moisture
- 16" x 10' Flexible urethane intake hose increases volume
- Metal discharge chute (12" x 6')

Mounting Options:

- Skid or Tow-Behind

For more info call
1300 333 ACS



Litter & Leaf Vacuuming made easy

Model No.	8143-03-01	8183-04-01 8184-04-01	8293-04-01 8295-04-01	8353-04-01 8355-04-01	8363-05-01 8365-05-01
Engine	Subaru® EX40	B&S Vanguard™			Yanmar® Diesel
Displacement*	14HP	18HP	29HP	35HP	36HP
Mount	Skid (standard) (Optional Hitch, Swing-Away and Tailgate)	Skid Mount Swing-Away	Skid Mount/Tow Behind		
Hitch Class Requirements	Class III or IV Hitch Required for 2" Square Receiver	Class III Hitch Required for 2" Square Receiver (Skid Mount)	Class III Hitch Required for 2" Square Receiver 2-5/16 Ball Hitch Required for Optional Trailer Mount		
Starter	Pull	Electric / Pull	Electric		
Fuel System	7 Litres	18.9 Litres	22.7 Litres	26.50 Litres	
Fuel Type	Petrol				Diesel
Battery	N/A	12V		12V	12V
Impeller	16" Dia., 4 - 5/16" Teethed Steel Blades	20" dia., 4 - 3/8" Teethed Steel Blades		25" dia., 4 - 1/2" Teethed Steel Blades	
CFM	2803	3510	4710	6950	7450
Housing Liners	440 Belt	4.76mm Steel	6.35mm Steel	6.35mm Steel	
Intake Hose	8" x 10'	10" x 10'	12" x 10'	16" x 10'	
Discharge	Polymer 7" x 30"	Metal 7" x 30"	Flex-Tube 8" x 5'	Metal 12" x 6'	
Axle / Suspension	N/A		N/A Torflex® 907Kg	N/A Torflex® 1588 Kg	
Tire / Wheel	N/A		N/A ST205 / 75 D15		
Dry Weight	225 lbs.	209 Kg 263 Kg	329.8 Kg 494.4 Kg	523.9 Kg 705.3 Kg	766.57 Kg 948 Kg

What makes a Monster TruckLoader's real beasts? A four blade steel impeller with shredding teeth on all three debris touch points provides the best shredding ratio in the industry—**UP TO A MONSTROUS 15 to 1.**

