

# Villo Industrial Vacuum Cleaners

## VTDF



240 Volt & 415 Volt  
Full stainless steel construction  
HEPA Filtration (Optional)  
Side channel blower  
72dba at 2 metres  
Dust container capacity 35L  
1.3m<sup>2</sup> Filter area  
1.5Kw-2.2kW  
Max air flow of 210-265m<sup>3</sup>/h  
40mm air inlet diameter  
71cm x 41cm x 70 cm  
Weight 46-55kg

## V3



240 Volt , 15 AMP  
Three motor bypass 3600 watts  
Stainless steel container  
HEPA Filtration (Optional)  
85dba at 2 metres  
Container capacity 65L  
2.4-3.5m<sup>2</sup> Filter area  
3.6kW  
Max air flow of 480m<sup>3</sup>/h  
50mm air inlet diameter  
78cm x 67cm x 146cm  
Weight 115-135kg

## VKD



240 Volt & 415 Volt  
Stainless steel container  
HEPA Filtration (Optional)  
Side channel blower  
74-76dba at 2 metres  
Container capacity 65L  
2.4m<sup>2</sup> Filter area  
2.2Kw-4kW  
Max air flow of 265-420m<sup>3</sup>/h  
50mm air inlet diameter  
76-78 x 65-67 x 146-157cm  
Weight 134-178kg

## VZ



415 Volt  
Stainless steel container  
HEPA Filtration (Optional)  
Side channel blower  
72-78dba at 2 metres  
Container capacity 65-100L  
2.4m<sup>2</sup> Filter area  
2.2Kw-7.5kW  
Max air flow of 265-700m<sup>3</sup>/h  
50mm air inlet diameter  
118-130 x 67 x 132-152cm  
Weight 120-174kg

## VZF



415 Volt  
Stainless steel container  
HEPA Filtration (Optional)  
Side channel blower  
Reverse pulse filter cleaning  
72-78dba at 2 metres  
Container capacity 65-100L  
5.1m<sup>2</sup> Filter area  
2Kw-7.5kW  
Max air flow of 265-700m<sup>3</sup>/h  
50mm air inlet diameter  
118-130cm x 67cm x 137-157cm  
Weight 120-190kg

## VG



Pneumatic vacuum system  
Stainless steel container  
HEPA Filtration (Optional)  
74dba at 2 metres  
Container capacity 65L  
3.5m<sup>2</sup> Filter area  
15L/Sec air consumption  
Max air flow of 310m<sup>3</sup>/h  
50mm air inlet diameter  
78cm x 75cm x 143 cm  
Weight 72kg

## VZS-P



415 Volt  
Stainless steel container  
HEPA Filtration (Optional)  
Side channel blower  
72-78dba at 2 metres  
Dust container capacity 65-100L  
3.5m<sup>2</sup> Filter area  
2-7.5kW  
Max air flow of 156-412m<sup>3</sup>/h  
Explosion proof motor  
50mm air inlet diameter  
118-130cm x 67cm x 132-152cm  
Weight 140-186kg

## VKY



415 Volt  
2.2Kw - 3.0Kw  
Side channel blower  
74-76dba at 2 metres  
Self priming  
CNC oil Collection  
Solids container capacity 30L  
Oil container capacity 100L  
Max air flow of 265-318m<sup>3</sup>/h  
Industrial Castors  
50mm air inlet diameter  
78cm x 74cm x 163-170 cm  
Weight 116-136kg

For more info call  
**1300 333 ACS**



# Industrial Vacuum Cleaning made *easy*

## VB



2 x 120Ah Battery Deep Cycle  
2.5hrs run time full load  
Stainless steel container  
HEPA Filtration (Optional)  
76dba at 2 metres  
Container capacity 70L  
1.8m<sup>2</sup> Filter area  
2 x 0.5kW motors  
Max air flow of 265m<sup>3</sup>/h  
40mm air inlet diameter  
88cm x 47cm x 119 cm  
Weight 120kg

## VKF



415 Volt  
Stainless steel container  
HEPA Filtration (Optional)  
Side channel blower  
74dba at 2 metres  
Container capacity 65L  
3.5m<sup>2</sup> Filter area  
Vibrating filter cleaner  
2.2kW  
Max air flow of 265m<sup>3</sup>/h  
50mm air inlet diameter  
75cm x 67cm x 162cm  
Weight 104kg

## VY 350



415 Volt  
Stainless steel container  
Large capacity  
Side channel blower  
76dba at 2 metres  
Solids container capacity 30L  
Oil container capacity 350L  
4kW  
Max air flow of 318m<sup>3</sup>/h  
50mm air inlet diameter  
140cm x 63cm x 137.5 cm  
Weight 185kg

## VS-J



415 Volt  
Wet and Dry Industrial Vacuum  
Stainless steel container  
Side channel blower  
74dba at 2 metres  
Dust container capacity 80L  
1.5-1.8m<sup>2</sup> Filter area  
4kW  
Max air flow of 318m<sup>3</sup>/h  
40mm air inlet diameter  
57cm x 120cm x 95cm  
Weight 80-85kg

## ACCESSORIES

### S SHAPE ALUMINIUM DOUBLE BEND

VLTB-5011  
Brush connector,  
can match with VLFT-5011



### CONNECTION EXTENSION TUBE

VLTB-1204  
Diameter: Ø50MM  
Length:100CM,aluminum surface oxidation treatment  
The tube can connect end to end and reach 90cm



### ONE WAY AIR INLET VALVE



### DUST BRUSH

VLFT-5011  
Diameter: Ø50MM  
Work width:430MM  
Match with Aluminium double bend VLTB-5011  
Aluminum die casting, full metal accessories



### HOSE CONNECTOR

VLTB-1037  
Diameter: Ø50MM  
Match with suction hose VLRG-5011  
Used for connecting two Ø50MM suction hose  
Dimension:50MM\*130MM Aluminum oxidation treated



### 3 x 38MM FOUR-WAY CONNECTION SUCTION INLET



### WATER BRUSH

VLFT-5022  
Diameter: Ø50MM  
Work width:550MM  
Match with Aluminium double bend VLTB-5011  
Aluminum die casting, full metal accessories



### HOSE CONNECTOR

VLPA-5011  
Diameter: Ø50MM  
Match with VLRG-5011



### VARIOUS FILTERS



### HOSE CONNECTOR

VLPA-5011  
Diameter: Ø50MM  
Match with VLRG-5011



### ROUND BRUSH

VLFT-5031  
Diameter: Ø50MM  
Match with VLRG-5011



### ASPORATION FLAT MOUTH

VLFT-1043  
Diameter: Ø50MM  
Length:50CM,aluminum surface oxidation treatment  
Type: Front beveling and flank beveling



### SUCTION HOSE

VLRG-5011  
Match with VLPA-5011

